

View Online at <https://aerobasegroup.com/nsn/5905-00-581-3640>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

Between 0.7490 inches and 0.7500 inches

**Pilot Length:**

0.0620 inches

**Overall Length:**

2.671 inches

**Undercut Diameter:**

2.000 inches

**Undercut Width:**

0.0620 inches

**Body Diameter:**

2.000 inches

**Angle Of Mounting Hole In Deg:**

60.0

**Angle Between Centerlines Of Mounting Holes In Deg:**

120.000

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.625 inches

**Body Length:**

Between 1.953 inches and 2.015 inches

**Overall Diameter:**

2.000 inches

**Mounting Lip Diameter:**

Between 1.8740 inches and 1.8750 inches

**Mounting Lip Depth:**

0.0620 inches

**Mounting Hole/stud Circle Diameter:**

1.250 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Ball

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

3600.0

**Maximum Starting Torque:**

1.50 inch-ounces

**Maximum Running Torque:**

1.00 inch-ounces

**Screw Thread Diameter:**

0.164 inches

**Screw Thread Series Designator:**

Unc

**Screw Thready Qty Per Inch (tpi):**

32.0

**Mounting Facility Quantity:**

3

**Terminal Location:**

Longitudinally positioned on the circumference

**Mounting Method:**

Threaded hole

**Features Provided:**

Nonmetallic shaft

**Electrical Resistance Per Section:**

10.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

3600.0

**Function Conformity Tolerance Per Section:**

-0.10/+0.10 single section

**Power Dissipation Rating Per Section In Watts:**

3.5 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Fixed Tap Quantity Per Section:**

1 single section

**Tap Location Tolerance Per Section:**

-0.5/+0.5 ohms single section

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Tap Location From Ccw Terminal Per Section In Ohms:**

5000.0 single section

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

50.0 single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0