

View Online at <https://aerobasegroup.com/nsn/5905-00-581-3645>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 1.8740 inches and 1.8750 inches

Pilot Length:

0.0620 inches

Overall Length:

1.593 inches

Undercut Diameter:

1.875 inches

Undercut Width:

0.0620 inches

Body Diameter:

2.000 inches

Angle Of Mounting Hole In Deg:

60.0

Angle Between Centerlines Of Mounting Holes In Deg:

120.0

Shaft Diameter:

Between 0.249 inches and 0.250 inches

Shaft Length:

0.625 inches

Body Length:

0.969 inches

Overall Diameter:

2.240 inches

Mounting Lip Diameter:

2.0000 inches

Mounting Lip Depth:

0.0620 inches

Mounting Hole/stud Circle Diameter:

1.250 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

356.0

Maximum Starting Torque:

1.20 inch-ounces

Maximum Running Torque:

0.60 inch-ounces

Screw Thread Diameter:

0.164 inches

Screw Thread Series Designator:

Unc

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Facility Quantity:

3

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Threaded hole

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

40.0 kilohms single section

Tap Location From Cw Terminal Per Section In Deg Of Effective Electrical Rotation:

188.0 single section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.10/+0.10 single section

Power Dissipation Rating Per Section In Watts:

2.8 free air single section

Function Conformity Per Section:

Single section independent linearity

Fixed Tap Quantity Per Section:

1 single section

Tap Location Tolerance Per Section:

-1.0/+1.0 degrees angular rotation single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

Special Features:

Tap terminal connected to cw terminal to provide 21124.0 ohm nom resistance

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0