

View Online at <https://aerobasegroup.com/nsn/5905-00-581-3819>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

2.375 inches

**Body Diameter:**

1.500 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.875 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

1.500 inches

**Overall Diameter:**

1.500 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Bearing

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

3600.0

**Maximum Starting Torque:**

2.00 inch-ounces

**Maximum Running Torque:**

1.50 inch-ounces

**Maximum Stop Torque:**

500.00 inch-ounces

**Nonturn Device Location:**

At 12 oclock

**Nonturn Device Radius:**

0.531 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Front end

**Mounting Method:**

Standard bushing

**Features Provided:**

Nonmetallic shaft

**Electrical Resistance Per Section:**

2.5 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

360.00

**Function Conformity Tolerance Per Section:**

-1.00/+1.00 single section

**Power Dissipation Rating Per Section In Watts:**

1.5 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

71.0 single section

**Terminal Type And Quantity:**

3 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0