## NSN 5905-00-581-4907

Nonprecision Wire Wound Variable Resistor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5905-00-581-4907



**Section Quantity:** First Flat Length: 0.438 inches Flat Height: 0.219 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.000 inches **Mounting Bushing Length:** 0.375 inches **Overall Diameter:** 2.750 inches **Shaft Style:** Round, flatted **Contact Arm Electrical Off Position:** Fully ccw **Actuator Type:** Single shaft **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.500 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 25.000 ohms single section **Resistance Tolerance Per Section In Percent:** -5.0 to 15.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 2 screw Shelf Life:

N/a

## NSN 5905-00-581-4907

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A002a0