## NSN 5905-00-581-7451

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-581-7451

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Overall Length:
1.344 inches
Overall Height:
0.344 inches
Overall Width:
0.312 inches
Mounting Hole Diameter:
Between 0.088 inches and 0.108 inches
Shaft Length:
Between 0.046 inches and 0.078 inches
Body Length:
Between 0.955 inches and 1.005 inches
Body Width:
0.312 inches
Body Height:
0.344 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Lateral Distance Between Mounting Hole Centers:
0.281 inches
Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Unthreaded hole
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
100.000 ohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-1.0/+1.0 single section

## NSN 5905-00-581-7451

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Offit Of Weasure.
 Demilitarization:

Fiig: A002a0