NSN 5905-00-581-7598

Inductive Wire Wound Fixed Resistor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5905-00-581-7598 |
|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
| -260.0/+260.0 |
| Electrical Resistance: |
| 100.000 ohms |
| Resistance Tolerance In Percent: |
| -5.000/+5.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 25.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 350.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+350.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Type: |
| Tab, solder lug |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.484 inches |
| Body Diameter: |
| 0.906 inches |
| Body Length: |
| Between 3.938 inches and 4.062 inches |
| Power Dissipation Rating In Watts: |
| 55.000 free air |
| Terminal Width: |
| Between 0.172 inches and 0.328 inches |
| Cubic Measure (non-core): |
| 2.578 cubic inches |
| Criticality Code Justification: |
| Feat |
| Special Features: |
| Sea-knight helicopter |
| Unpackaged Unit Weight: |
| 40.5 grams |
| Style Designator: |
| Radial terminal each end |
| Test Data Document: |
| 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |

Specification Data:

81349-mil-r-26/3 government specification

and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5905-00-581-7598

Inductive Wire Wound Fixed Resistor - Page 2 of 2



| Sh | elf | Life: |
|----|-----|-------|
| | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0