NSN 5905-00-581-7937

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-581-7937 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.702 inches First Flat Length: 0.344 inches Flat Height: 0.216 inches **Body Diameter:** 3.190 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.780 inches **Overall Diameter:** 3.785 inches **Shaft Style:** Round, flatted **Contact Arm Electrical Off Position:** Fully ccw **Actuator Type:** Single shaft **Maximum Starting Torque:** 48.00 inch-ounces **Maximum Stop Torque:** 140.00 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.500 inches **Screw Thread Diameter:** 0.375 inches

Screw Thread Series Designator: Unef

NSN 5905-00-581-7937

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
10.0 ohms single section
Rotary Actuator Travel In Angular Deg:
Between 295.0 and 315.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
340.0 single section
Power Dissipation Rating Per Section In Watts:
100.0 heat sink single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-22/8 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A002a0