Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-581-7992

Section Quantity: 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** Between 2.999 inches and 3.311 inches **Body Diameter:** Between 1.500 inches and 1.710 inches Shaft Diameter: Between 0.248 inches and 0.251 inches Shaft Length: 2.500 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** Between 0.530 inches and 0.780 inches **Overall Diameter:** 2.135 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 0.531 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Stop Torque:** 128.00 inch-ounces **Nonturn Device Location:** At 9 oclock **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:**

Standard bushing

NSN 5905-00-581-7992

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:

1.5 kilohms single section

Rotary Actuator Travel In Angular Deg:

Between 280.0 and 305.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

Power Dissipation Rating Per Section In Watts:

4.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-19 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

81349-mil-r-19/3 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0