## NSN 5905-00-583-2070

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-583-2070

| -350.0/+0.0  Electrical Resistance:  47.000 ohms  Resistance Tolerance In Percent: -1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power:  40.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 140.0 |
|--|
| 47.000 ohms  Resistance Tolerance In Percent: -1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 40.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:   |
| Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 40.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| -1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power:  40.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 40.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:   |
| 40.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
|  |
| 140.0  |
|  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:   |
| -55.0/+140.0   |
| Inclosure Method:  |
| Hermetically sealed  |
| Terminal Type:   |
| Wire lead  |
| Reliability Indicator:   |
| Not established  |
| Body Diameter:   |
| 0.390 inches   |
| Body Length:   |
| 1.875 inches   |
| Power Dissipation Rating In Watts:   |
| 1.000 free air   |
| Special Features:  |
| Inert gas filled   |
| Style Designator:  |
| Axial terminal each end  |
| Test Data Document:  |
| 18876-8519308 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.  |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing)  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A001a0   |