NSN 5905-00-583-2420

Section Quantity:

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-583-2420

I
Body Style:
Cylindrical bushing mounted
First Flat Length:
0.344 inches
Flat Height:
0.219 inches
Body Diameter:
1.562 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.375 inches
Body Length:
1.375 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Nonturn Device Location:
At 6 oclock
Nonturn Device Radius:
0.500 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Locking bushing
Electrical Resistance Per Section:
100.000 ohms single section
Power Dissipation Rating Per Section In Watts:
25.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Standard Taper Curve Per Section:
A single section

NSN 5905-00-583-2420

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal	Туре	And	Quantity:
ı erminai	туре	Ana	Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0