## NSN 5905-00-583-6212

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-583-6212 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 3.957 inches First Flat Length: 1.969 inches Flat Height: Between 0.211 inches and 0.221 inches **Body Diameter:** 1.680 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** Between 2.453 inches and 2.457 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.410 inches **Overall Diameter:** 2.260 inches **Shaft Style:** Round, flatted **Contact Arm Electrical Off Position:** Fully ccw **Actuator Type:** Single shaft **Maximum Starting Torque:** 40.00 inch-ounces **Maximum Stop Torque:** 240.00 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** Between 0.485 inches and 0.515 inches

**Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef

## NSN 5905-00-583-6212

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
2
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
350.0 ohms single section
Rotary Actuator Travel In Angular Deg:
Between 275.0 and 305.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
340.0 single section
Power Dissipation Rating Per Section In Watts:
25.0 heat sink single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-milr22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No
Fiig:
A002a0