NSN 5905-00-583-6941

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-583-6941 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.109 inches **Terminal Length:** 0.188 inches **Body Diameter:** 1.469 inches **Shaft Diameter:** Between 0.248 inches and 0.250 inches **Shaft Length:** 0.562 inches **Body Length:** 0.500 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Locking bushing **Electrical Resistance Per Section:** 1.500 kilohms single section

Power Dissipation Rating Per Section In Watts:

7.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

NSN 5905-00-583-6941

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section
A single section
Special Features:
0.438 bushing length
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0