## NSN 5905-00-583-7625

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-583-7625

view Online at https://aerobasegroup.com/nsn/5905-00-565-7625
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
2.000 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.625 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.625 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
270.0
270.0  Nonturn Device Location:
Nonturn Device Location:
Nonturn Device Location: At 9 oclock
Nonturn Device Location: At 9 oclock Nonturn Device Radius:
Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.531 inches
Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter:
Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches
Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator:
Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef
Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi):
Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0
Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location:
Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Rear end
Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Rear end Mounting Method:
Nonturn Device Location:  At 9 oclock  Nonturn Device Radius:  0.531 inches  Screw Thread Diameter:  0.375 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Terminal Location:  Rear end  Mounting Method:  Standard bushing
Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Rear end Mounting Method: Standard bushing Electrical Resistance Per Section:
Nonturn Device Location: At 9 oclock Nonturn Device Radius: 0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Rear end Mounting Method: Standard bushing Electrical Resistance Per Section: 2.5 megohms single section

85.0 single section

## NSN 5905-00-583-7625

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No