NSN 5905-00-583-7768

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-583-7768 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.3125 inches Pilot Length: 0.0620 inches **Overall Length:** 3.234 inches First Flat Length: 0.200 inches Flat Height: 0.219 inches **Undercut Diameter:** 1.312 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 1.437 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.625 inches **Body Length:** 1.984 inches **Overall Diameter:** 1.938 inches **Mounting Lip Diameter:** 1.4370 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round, flatted **Shaft Bearing Type:** Ball **Actuator Type:** Double ended shaft

Effective Electrical Rotation In Deg Angular Rotation:

354.0

NSN 5905-00-583-7768

Precision Wire Wound Variable Resistor - Page 2 of 3



Maximum Starting Torque:
4.00 inch-ounces
Maximum Running Torque:
2.00 inch-ounces
Shaft End Play:
0.005 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.004 inches
Pilot Diameter Runout:
0.00200 inches
Shaft Radial Play:
0.004 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
5.0 percent, rated amperes c and better
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.20/+0.20 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 all sections
Power Dissipation Rating Per Section In Watts:
2.0 7th secondary at 10'30 oclock
Function Conformity Per Section:
All sections independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 all sections
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
6 oclock all primaries
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 all sections
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Terminal Type And Quantity:
6 turret
Shelf Life:
N/a

NSN 5905-00-583-7768

Precision Wire Wound Variable Resistor - Page 3 of 3



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0