

View Online at <https://aerobasegroup.com/nsn/5905-00-583-7808>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

1.266 inches

Shaft Diameter:

0.265 inches

Shaft Length:

Between 0.469 inches and 0.781 inches

Mounting Bushing Length:

0.469 inches

Body Length:

1.516 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Nonturn Device Location:

At 6 oclock and at 9 oclock

Nonturn Device Radius:

0.531 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

10.0 kilohms all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 all sections

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 all sections

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

55.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0