

View Online at <https://aerobasegroup.com/nsn/5905-00-583-8449>

Section Quantity:

1

Body Style:

Cylindrical hole/slot mounted

Reliability Indicator:

Not established

Body Diameter:

3.000 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.969 inches

Body Length:

1.234 inches

Mounting Hole/stud Circle Diameter:

1.750 inches

Shaft Style:

Round

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

340.0

Maximum Starting Torque:

0.50 inch-ounces

Maximum Running Torque:

0.25 inch-ounces

Shaft Runout:

0.001 inches

Lateral Runout:

0.001 inches

Pilot Diameter Runout:

0.00100 inches

Screw Thread Diameter:

0.138 inches

Screw Thread Series Designator:

Unc

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Facility Quantity:

3

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Threaded hole

Electrical Resistance Per Section:

50.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.50/+0.50 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

80.0 single section

Power Dissipation Rating Per Section In Watts:

12.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0