

View Online at <https://aerobasegroup.com/nsn/5905-00-583-8722>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

4.647 inches

**Body Diameter:**

0.625 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

1.974 inches

**Mounting Bushing Length:**

0.250 inches

**Body Length:**

2.676 inches

**Overall Diameter:**

1.188 inches

**Undercut Diameter:**

0.125 inches

**Shaft Style:**

Round, stepped

**Switch Type:**

Push

**Switch Voltage Rating In Volts:**

125.0

**Actuator Type:**

Dual concentric

**Effective Electrical Rotation In Deg Angular Rotation:**

333.0

**Nonturn Device Location:**

At 6 oclock

**Nonturn Device Radius:**

0.229 inches

**Switch Operating Position:**

Any position of rotation travel

**Switch Contact Arrangement:**

Double pole, double throw

**Undercut Length:**

1.000 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thread Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over more than half the circumference

**Mounting Method:**

Standard bushing

**Features Provided:**

Switch

**Electrical Resistance Per Section:**

5.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

333.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

120.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-70.0 to 70.0 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Switch Current Type And Rating In Amps:**

3.000 ac/dc

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0