NSN 5905-00-583-8795

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-583-8795 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.313 inches **Overall Height:** 0.300 inches **Overall Width:** 0.280 inches **Mounting Hole Diameter:** 0.086 inches **Shaft Diameter:** 0.130 inches **Shaft Length:** 0.062 inches **Body Length:** 1.240 inches **Body Width:** 0.240 inches **Body Height:** 0.300 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Lateral Distance Between Mounting Hole Centers:** 0.995 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:**

1.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

9000.0

NSN 5905-00-583-8795

Demilitarization:

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -1.0 to 1.0 single section **Power Dissipation Rating Per Section In Watts:** 0.6 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 50.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a **Unit Of Measure:**