NSN 5905-00-586-6986

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-586-6986

| Section Quantity: |
|---|
| 1 |
| Body Style: |
| Cylindrical bushing mounted |
| Reliability Indicator: |
| Not established |
| Body Diameter: |
| 0.484 inches |
| Shaft Diameter: |
| 0.250 inches |
| Shaft Length: |
| 1.000 inches |
| Mounting Bushing Length: |
| 0.250 inches |
| Body Length: |
| 0.312 inches |
| Shaft Style: |
| Round |
| Actuator Type: |
| Single shaft |
| Effective Electrical Rotation In Deg Angular Rotation: |
| 320.0 |
| Maximum Starting Torque: |
| 1.00 inch-ounces |
| Maximum Running Torque: |
| 0.50 inch-ounces |
| Screw Thread Diameter: |
| 0.375 inches |
| Screw Thread Series Designator: |
| Unef |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Terminal Location: |
| Radially positioned over less than half the circumference |
| Mounting Method: |
| Standard bushing |
| Electrical Resistance Per Section: |
| 5.0 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 360.0 |
| Function Conformity Tolerance Per Section: |

-0.50/+0.50 single section

NSN 5905-00-586-6986

Fiig: A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 80.0 single section **Power Dissipation Rating Per Section In Watts:** 3.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Continuous motion **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:** No