NSN 5905-00-587-0482

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-587-0482 **Section Quantity: Reliability Indicator:** Not established **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.500 inches **Mounting Bushing Length:** 0.375 inches **Overall Diameter:** 1.625 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 3.00 inch-ounces **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 6.300 kilohms single section **Function Conformity Tolerance Per Section:** -0.10/+0.10 single section **Power Dissipation Rating Per Section In Watts:** 5.0 free air single section **Function Conformity Per Section:**

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-3.0/+3.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Terminal Type And Quantity:

3 tab, solder lug

NSN 5905-00-587-0482

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0