NSN 5905-00-587-0760

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-587-0760

Section Quantity:							
1							
Body Style:							
Cylindrical bushing mounted							
Reliability Indicator:							
Not established							
Body Diameter:							
0.750 inches							
Shaft Diameter:							
0.125 inches							
Shaft Length:							
0.875 inches							
Body Length:							
0.375 inches							
Shaft Style:							
Round, slotted							
Actuator Type:							
Single shaft							
Nonturn Device Location:							
At 9 oclock							
Nonturn Device Radius:							
0.375 inches							
Screw Thread Diameter:							
0.250 inches							
Screw Thread Series Designator:							
Unef							
Screw Thready Qty Per Inch (tpi):							
32.0							
Mounting Method:							
Standard bushing							
Electrical Resistance Per Section:							
1.000 megohms single section							
Power Dissipation Rating Per Section In Watts:							
0.3 free air single section							
Resistance Tolerance Per Section In Percent:							
-30.0 to 30.0 single section							
Standard Taper Curve Per Section:							
X single section							
Terminal Type And Quantity:							
3 tab, solder lug							
Shelf Life:							

N/a

NSN 5905-00-587-0760

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A002a0