NSN 5905-00-588-8755

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-588-8755

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
Between 2.0570 inches and 2.0670 inches
Pilot Length: Between 0.1200 inches and 0.1300 inches
Overall Length:
2.473 inches
Undercut Diameter:
Between 2.630 inches and 2.760 inches
Undercut Width:
Between 0.1920 inches and 0.2020 inches
Body Diameter:
Between 2.995 inches and 3.005 inches
Angle Of Mounting Hole In Deg:
90.0
Angle Between Centerlines Of Mounting Holes In Deg:
180.0
Shaft Diameter:
Shaft Diameter: 0.375 inches
0.375 inches
0.375 inches Shaft Length:
0.375 inches Shaft Length: Between 1.090 inches and 1.150 inches
0.375 inches Shaft Length: Between 1.090 inches and 1.150 inches Body Length:
0.375 inches Shaft Length: Between 1.090 inches and 1.150 inches Body Length: Between 1.311 inches and 1.323 inches
0.375 inches Shaft Length: Between 1.090 inches and 1.150 inches Body Length: Between 1.311 inches and 1.323 inches Overall Diameter:
0.375 inches Shaft Length: Between 1.090 inches and 1.150 inches Body Length: Between 1.311 inches and 1.323 inches Overall Diameter: 3.445 inches
0.375 inches Shaft Length: Between 1.090 inches and 1.150 inches Body Length: Between 1.311 inches and 1.323 inches Overall Diameter: 3.445 inches Mounting Lip Diameter:
0.375 inches Shaft Length: Between 1.090 inches and 1.150 inches Body Length: Between 1.311 inches and 1.323 inches Overall Diameter: 3.445 inches Mounting Lip Diameter: 3.1400 inches
0.375 inches Shaft Length: Between 1.090 inches and 1.150 inches Body Length: Between 1.311 inches and 1.323 inches Overall Diameter: 3.445 inches Mounting Lip Diameter: 3.1400 inches Mounting Lip Depth:
0.375 inches Shaft Length: Between 1.090 inches and 1.150 inches Body Length: Between 1.311 inches and 1.323 inches Overall Diameter: 3.445 inches Mounting Lip Diameter: 3.1400 inches Mounting Lip Depth: Between 0.1200 inches and 0.1300 inches
0.375 inches Shaft Length: Between 1.090 inches and 1.150 inches Body Length: Between 1.311 inches and 1.323 inches Overall Diameter: 3.445 inches Mounting Lip Diameter: 3.1400 inches Mounting Lip Depth: Between 0.1200 inches and 0.1300 inches Mounting Hole/stud Circle Diameter:
0.375 inches Shaft Length: Between 1.090 inches and 1.150 inches Body Length: Between 1.311 inches and 1.323 inches Overall Diameter: 3.445 inches Mounting Lip Diameter: 3.1400 inches Mounting Lip Depth: Between 0.1200 inches and 0.1300 inches Mounting Hole/stud Circle Diameter: Between 1.490 inches and 1.510 inches
0.375 inches Shaft Length: Between 1.090 inches and 1.150 inches Body Length: Between 1.311 inches and 1.323 inches Overall Diameter: 3.445 inches Mounting Lip Diameter: 3.1400 inches Mounting Lip Depth: Between 0.1200 inches and 0.1300 inches Mounting Hole/stud Circle Diameter: Between 1.490 inches and 1.510 inches Shaft Style:
0.375 inches Shaft Length: Between 1.090 inches and 1.150 inches Body Length: Between 1.311 inches and 1.323 inches Overall Diameter: 3.445 inches Mounting Lip Diameter: 3.1400 inches Mounting Lip Depth: Between 0.1200 inches and 0.1300 inches Mounting Hole/stud Circle Diameter: Between 1.490 inches and 1.510 inches Shaft Style: Round
0.375 inches Shaft Length: Between 1.090 inches and 1.150 inches Body Length: Between 1.311 inches and 1.323 inches Overall Diameter: 3.445 inches Mounting Lip Diameter: 3.1400 inches Mounting Lip Depth: Between 0.1200 inches and 0.1300 inches Mounting Hole/stud Circle Diameter: Between 1.490 inches and 1.510 inches Shaft Style: Round Actuator Type:
0.375 inches Shaft Length: Between 1.090 inches and 1.150 inches Body Length: Between 1.311 inches and 1.323 inches Overall Diameter: 3.445 inches Mounting Lip Diameter: 3.1400 inches Mounting Lip Depth: Between 0.1200 inches and 0.1300 inches Mounting Hole/stud Circle Diameter: Between 1.490 inches and 1.510 inches Shaft Style: Round Actuator Type: Single shaft

NSN 5905-00-588-8755

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft Runout:
0.001 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.00150 inches
Shaft Radial Play:
0.001 inches
Screw Thread Diameter:
0.138 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
3
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Threaded hole
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
28.27 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-2.00/+2.00 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section 360 degrees cosine
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:

-

NSN 5905-00-588-8755

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0