

View Online at <https://aerobasegroup.com/nsn/5905-00-588-8994>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.594 inches

Body Diameter:

1.156 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.969 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.625 inches

Overall Diameter:

1.344 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

280.0

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

End Application:

Missile air-to air phoeni (aim-54), strategic weapons systems (poseidon and trident)

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

300.0 ohms single section

Rotary Actuator Travel In Angular Deg:

300.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Stops

Criticality Code Justification:

Feat

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-40.0 to 40.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Special Features:

Weapon system essential

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0