## NSN 5905-00-589-9972

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-589-9972 **Section Quantity:** 2 **Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** 1.875 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.375 inches **Body Length:** 1.938 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 320.0 **Screw Thread Diameter:** 0.138 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity: Terminal Location:** Lower adjacent side single row **Mounting Method:** Threaded hole **Electrical Resistance Per Section:** 3.48 kilohms 2nd section **Rotary Actuator Travel In Angular Deg:** Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 all sections

**Power Dissipation Rating Per Section In Watts:** 

0.250 free air all sections

**Resistance Tolerance Per Section In Percent:** 

-1.0 to 1.0 all sections

## NSN 5905-00-589-9972

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 all sections
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
4 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No