

View Online at <https://aerobasegroup.com/nsn/5905-00-592-1814>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

Between 0.4370 inches and 0.4375 inches

**Pilot Length:**

0.0620 inches

**Undercut Diameter:**

Between 0.4370 inches and 0.4375 inches

**Undercut Width:**

0.0620 inches

**Body Diameter:**

0.500 inches

**Shaft Diameter:**

Between 0.1245 inches and 0.1248 inches

**Shaft Length:**

0.500 inches

**Body Length:**

0.688 inches

**Mounting Lip Diameter:**

0.5000 inches

**Mounting Lip Depth:**

0.0620 inches

**Shaft Style:**

Round

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

325.0

**Maximum Starting Torque:**

2.00 inch-ounces

**Maximum Running Torque:**

2.00 inch-ounces

**Terminal Location:**

Radially positioned over more than half the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

50.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-0.75/+0.75 single section

**Power Dissipation Rating Per Section In Watts:**

2.5 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

60.0 single section

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0