NSN 5905-00-593-7535

Mil-r-15109 spec.

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-593-7535

| Electrical Resistance: |
|--|
| 19.570 ohms |
| Resistance Tolerance In Percent: |
| -10.000/+10.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 50.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 425.0 |
| Inclosure Method: |
| Uninclosed |
| Terminal Type: |
| Tab, solder lug |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.062 inches |
| Body Diameter: |
| 2.000 inches |
| Body Length: |
| 15.062 inches |
| Power Dissipation Rating In Watts: |
| 470.000 free air |
| Terminal Width: |
| 1.000 inches |
| Cubic Measure (non-core): |
| 47.318 cubic inches |
| Style Designator: |
| Radial terminal each end |
| Test Data Document: |
| 81349-mil-r-15109 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A001a0 |
| Mil-std (military Standard): |