

View Online at https://aerobasegroup.com/nsn/5905-00-593-8074

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

2.87500 inches

Pilot Length:

0.06200 inches

Overall Length:

1.657 inches

Undercut Diameter:

2.875 inches

Undercut Width:

0.07800 inches

Body Diameter:

3.000 inches

Angle Of Mounting Hole In Deg:

90.0

Angle Between Centerlines Of Mounting Holes In Deg:

120.0

Shaft Diameter:

0.2495 inches

Shaft Length:

0.469 inches

Body Length:

1.188 inches

Overall Diameter:

3.390 inches

Mounting Lip Diameter:

3.00000 inches

Mounting Lip Depth:

0.09300 inches

Mounting Hole/stud Circle Diameter:

1.750 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft



Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

2.00 inch-ounces

Maximum Running Torque:

1.50 inch-ounces

Shaft End Play:

0.00500 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.001 inches

Pilot Diameter Runout:

0.00100 inches

Shaft Radial Play:

0.001 inches

Screw Thread Diameter:

0.164 inches

Screw Thread Series Designator:

Unc

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Facility Quantity:

3

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Threaded hole

Electrical Resistance Per Section:

56.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

3600.0

Function Conformity Tolerance Per Section:

-0.25/+0.25 single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Power Dissipation Rating Per Section In Watts:

1.5 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Precision Wire Wound Variable Resistor - Page 3 of 3



Actuator Travel Control Feature:

Clutch

Function Characteristic Per Section:

Single section linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0