NSN 5905-00-593-8223

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-593-8223

Section Quantity:
1

Body Style:
Cylindrical servo mounted

Pilot Diameter:
Between 2.8740 inches and 2.8750 inches
Pilot Length:

0.0630 inchesOverall Length:1.705 inches

Undercut Diameter:

Reliability Indicator:

Not established

2.874 inches

Undercut Width:

0.0730 inches

Body Diameter:

3.000 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.625 inches

Body Length:

1.049 inches

Overall Diameter:

3.000 inches

Mounting Lip Diameter:

3.0000 inches

Mounting Lip Depth:

0.0930 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Ball

Actuator Type:

Double ended shaft

Effective Electrical Rotation In Deg Angular Rotation:

358.0

Maximum Starting Torque:

1.50 inch-ounces

Maximum Running Torque:

0.70 inch-ounces

NSN 5905-00-593-8223

Precision Wire Wound Variable Resistor - Page 2 of 2



Shaft End Play:
0.0025 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.002 inches
Shaft Radial Play:
0.002 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
5.0 free air single section
Function Conformity Per Section:
Single section absolute linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A002a0