

View Online at <https://aerobasegroup.com/nsn/5905-00-593-8227>

**Section Quantity:**

7

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

Between 2.8740 inches and 2.8750 inches

**Pilot Length:**

0.0620 inches

**Overall Length:**

5.214 inches

**Undercut Diameter:**

2.874 inches

**Undercut Width:**

0.0730 inches

**Body Diameter:**

3.000 inches

**Shaft Diameter:**

Between 0.249 inches and 0.250 inches

**Shaft Length:**

0.594 inches

**Body Length:**

4.433 inches

**Mounting Lip Diameter:**

3.0000 inches

**Mounting Lip Depth:**

0.0930 inches

**Shaft Style:**

Round, slotted

**Shaft Bearing Type:**

Ball

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

358.0

**Maximum Starting Torque:**

5.70 inch-ounces

**Maximum Running Torque:**

4.30 inch-ounces

**Shaft End Play:**

0.0025 inches

**Shaft Runout:**

0.001 inches

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Features Provided:**

Nonmetallic shaft

**Electrical Resistance Per Section:**

5.0 kilohms all sections

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-1.00/+1.00 all sections

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 all sections

**Power Dissipation Rating Per Section In Watts:**

2.0 free air all sections

**Function Conformity Per Section:**

All sections absolute conformity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 all sections

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

All sections table

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 all sections

**Test Data Document:**

10001-1225782 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

21 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0