

View Online at <https://aerobasegroup.com/nsn/5905-00-593-8253>

Section Quantity:

5

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 2.8740 inches and 2.8750 inches

Pilot Length:

0.0620 inches

Overall Length:

4.055 inches

Undercut Diameter:

2.825 inches

Undercut Width:

0.0730 inches

Body Diameter:

3.000 inches

Shaft Diameter:

0.249 inches

Shaft Length:

Between 0.594 inches and 0.656 inches

Body Length:

3.305 inches

Overall Diameter:

3.256 inches

Mounting Lip Diameter:

3.0000 inches

Mounting Lip Depth:

0.0930 inches

Shaft Style:

Round, slotted

Actuator Type:

Double ended shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 357.0 and 359.0

Maximum Starting Torque:

4.30 inch-ounces

Maximum Running Torque:

3.10 inch-ounces

Shaft End Play:

0.001 inches

Terminal Location:

Longitudinally positioned on the circumference

Mounting Method:

Clamp ring

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

5.0 megohms all sections

Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:

300.0 2nd section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-3.00/+3.00 1st section

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Fixed Tap Quantity Per Section:

2 5th section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 all sections

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

All sections table

Test Data Document:

10001-1472219 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

17 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0