

View Online at <https://aerobasegroup.com/nsn/5905-00-593-8255>

Section Quantity:

7

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 2.8740 inches and 2.8750 inches

Pilot Length:

0.0620 inches

Overall Length:

5.183 inches

Undercut Diameter:

Between 1.820 inches and 2.825 inches

Undercut Width:

0.0730 inches

Body Diameter:

3.000 inches

Shaft Diameter:

0.249 inches

Shaft Length:

Between 0.594 inches and 0.656 inches

Body Length:

4.433 inches

Body Height:

3.256 inches

Mounting Lip Diameter:

3.0000 inches

Mounting Lip Depth:

0.0930 inches

Shaft Style:

Round, slotted

Actuator Type:

Double ended shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 357.0 and 359.0

Maximum Starting Torque:

5.70 inch-ounces

Maximum Running Torque:

4.30 inch-ounces

Shaft Runout:

0.001 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

5.0 kilohms all sections

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-1.00/+1.00 all sections

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Function Conformity Per Section:

All sections independent linearity

Fixed Tap Quantity Per Section:

1 all sections

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 5th section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

All sections table

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Test Data Document:

10001-1472231 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

26 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0