NSN 5905-00-593-9354

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-593-9354 **Section Quantity: Body Style:** Rectangular w/bushing **Reliability Indicator:** Not established **Shaft Diameter:** 0.226 inches **Shaft Length:** 0.4688 inches **Mounting Bushing Length:** 0.4062 inches **Body Length:** 3.2188 inches **Body Width:** 3.9062 inches **Body Height:** 10.000 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Screw Thread Diameter:** 0.352 inches and 0.216 inches **Screw Thread Series Designator:** Unef and unc Screw Thready Qty Per Inch (tpi): 32.0 and 32.0 **Mounting Facility Quantity: Terminal Location:** Radially positioned over less than half the circumference

Mounting Method: Standard bushing and threaded hole **Electrical Resistance Per Section:** 500.0 ohms all sections **Rotary Actuator Travel In Angular Deg:**

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

350.0 all sections

NSN 5905-00-593-9354

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
12.5 free air all sections
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 all sections
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 all sections
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
12 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No