Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-594-2644

| Section Quantity: |
|---|
| 1 |
| Body Style: |
| Rectangular |
| Reliability Indicator: |
| Established |
| Reliability Failure Rate Level In Percent: |
| 0.100 |
| Terminal Length: |
| 0.300 inches |
| Shaft Diameter: |
| 0.075 inches |
| Shaft Length: |
| 0.080 inches |
| Body Length: |
| 0.420 inches |
| Body Width: |
| 0.170 inches |
| Body Height: |
| 0.375 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Center To Center Distance Between Terminals: |
| 0.200 inches |
| Terminal Location: |
| Rear end |
| Mounting Method: |
| Terminal |
| Electrical Resistance Per Section: |
| 25.0 kilohms single section |
| Center To Center Distance Between Center Terminal And Outside Terminal: |
| 0.100 inches |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 150.0 single section |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| -100.0 to 100.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 0.5 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -10.0 to 10.0 single section |
| |



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-39035 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 pin

Specification Data:

81349-mil-r-39035/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0