Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-594-3663

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.938 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

3.000 inches

#### Mounting Bushing Length:

0.375 inches

#### Body Length:

#### 0.516 inches

Shaft Style:

#### Round

Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

280.0

#### Nonturn Device Location:

At 9 oclock

#### Nonturn Device Radius:

0.438 inches

#### Screw Thread Diameter:

0.375 inches

#### **Screw Thread Series Designator:**

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

50.000 kilohms single section

# Rotary Actuator Travel In Angular Deg:

300.0

# Power Dissipation Rating Per Section In Watts:

0.25 free air single section



**Resistance Tolerance Per Section In Percent:** 

-20.0 to 20.0 single section

## Actuator Travel Control Feature:

Stops

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

### Fiig:

A002a0