Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-594-3668

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

### **Terminal Length:**

0.188 inches

### **Body Diameter:**

1.156 inches

Shaft Diameter:

Between 0.248 inches and 0.250 inches

Shaft Length:

0.500 inches

### Body Length:

0.625 inches

### **Overall Diameter:**

1.344 inches

Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

### Nonturn Device Location:

At 9 oclock

### Nonturn Device Radius:

0.531 inches

### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Radially positioned over less than half the circumference

## Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

100.000 ohms single section

# Power Dissipation Rating Per Section In Watts:

2.0 free air single section

# Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section



Standard Taper Curve Per Section:

A single section

### **Special Features:**

0.375 in. Long bushing

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

### Demilitarization:

No

#### Fiig:

A002a0