NSN 5905-00-594-3668

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-594-3668

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Terminal Length:
0.188 inches
Body Diameter:
1.156 inches
Shaft Diameter:
Between 0.248 inches and 0.250 inches
Shaft Length:
0.500 inches
Body Length:
0.625 inches
Overall Diameter:
1.344 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
Nonturn Device Radius: 0.531 inches
0.531 inches
0.531 inches Screw Thread Diameter:
0.531 inches Screw Thread Diameter: 0.375 inches
0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef
0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator:
0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi):
0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location:
0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference
0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method:
0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference
0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section:
0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 100.000 ohms single section
0.531 inches Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section:

-10.0 to 10.0 single section

NSN 5905-00-594-3668

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:
A single section
Special Features:
0.375 in. Long bushing
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0