NSN 5905-00-594-6130

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-594-6130

Section Quantity:
1
Body Style:
Rectangular bushing mounted
Reliability Indicator:
Not established
Mounting Bushing Length:
0.250 inches
Body Length:
1.313 inches
Body Width:
0.313 inches
Body Height:
0.360 inches
Actuator Type:
Flush drive with slot-hole
Screw Thread Diameter:
0.216 inches
Screw Thread Series Designator:
Unf
Screw Thready Qty Per Inch (tpi):
28.0
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.0 kilohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0 to 20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
80.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire loop

NSN 5905-00-594-6130

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

ion:

No

Fiig:

A002a0