NSN 5905-00-594-7297

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-594-7297

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: 100.0/+100.0 Electrical Resistance: 13.700 kilohms Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Range Of Tempurature Range Of Tempurature
Electrical Resistance: 13.700 kilohms Resistance Tolerance in Percent: 1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 125.0 Impurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Impurature Range Of Tempurature Coefficient in Deg Celsius: 50.001 Body Diameter: Body Length: Body Diameter: Body Di
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 10.001 Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 1.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 10.001 Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Tempurature Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 10.001 Body Diameter: 36theen 0.157 inches and 0.250 inches 36theen 0.157 inches and 0.656 inches Power Dissipation Rating In Watts: 10.250 free air Style Designator: Avial terminal each end Test Data Document: 31349-milr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 3etween 0.157 inches and 0.250 inches Body Length: 3etween 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Avial terminal each end Test Data Document: 31349-milr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-millr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-millr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.157 inches and 0.250 inches Bedween 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.256 free air Style Designator: Avial terminal each end Test Data Document: 81349-milr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Avial terminal each end Fest Data Document: 81349-milr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: B1349-milr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Reliability Failure Rate Level In Percent: 0.001 Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 01349-milr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: B1349-milr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: B1349-milr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 31349-milr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
D.250 free air Style Designator: Axial terminal each end Test Data Document: B1349-milr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Style Designator: Axial terminal each end Test Data Document: B1349-milr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Axial terminal each end Test Data Document: B1349-milr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Test Data Document: 31349-milr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
31349-milr55182/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
anvironmental and performance requirements and test conditions that are shown as "typical" "average" "" etc.)
situlo ilinental and performance requirements and test conditions that are shown as typical, average, , etc.).
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A001a0