## NSN 5905-00-596-2559

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-596-2559

Seedien Overditus
Section Quantity:
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Overall Length:
1.340 inches
Terminal Length:
0.187 inches
Overall Height:
0.593 inches
Overall Width:
0.343 inches
Mounting Hole Diameter:
0.086 inches
Body Length:
1.310 inches
Body Width:
0.343 inches
Body Height:
0.300 inches
Contact Arm Electrical Off Position:
Fully cw
Actuator Type:
Single shaft
Center To Center Distance Between Terminals:
0.680 inches
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Mounting Facility Quantity:
2
Terminal Location:
Right adjacent side single row
Mounting Method:
Unthreaded hole
Center To Center Distance Between Terminal Rows:
0.340 inches
Electrical Resistance Per Section:
50.000 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:

0.320 inches

## NSN 5905-00-596-2559

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 135.0 single section Power Dissipation Rating Per Section In Watts: 8.0 heat sink single section Resistance Tolerance Per Section In Percent: -2.0 to 2.0 single section Function Characteristic Per Section: Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 95.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A002a0