## NSN 5905-00-599-7929

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-599-7929

Electrical Resistance:  1.500 kilohms  Resistance Tolerance in Percent:  5.000/45.000  Ambient Tempurature in Deg Celsius At Full Rated Power:  135.0  Ambient Tempurature in Deg Celsius At Zero Percent Rated Power:  275.0  Tempurature Range Of Tempurature Coefficient in Deg Celsius:  65.0/+275.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  1.500 inches  Body Diameter:  0.000 inches  Body Diameter:  0.200 inches  Body Length:  1.500 free air  Style Designator:  Avaid terminal each end  Test Data Document:  27942-5807243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  We Unit Of Measure:  — Demilitarization:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 5.0004-5,000 Ambient Tempurature In Deg Celsius At Full Rated Power: 135.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/4275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Note established Terminal Length: 1.500 inches Baddy Length: 2.090 inches Baddy Length: 2.220 inches Power Dissipation Rating In Watts: 2.500 ree air Style Designator: Axial terminal each end Test Data Document: 97942-580r243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: Unit Of Measure: United	-10.0/+10.0
Resistance Tolerance In Percent: 5.000/45.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 135.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/4275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Note established Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end Test Data Document: 97942-580r243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: Wire Unit of Measure: Unit of Measure: Unit of Measure: United	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 135.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/4275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 97942-5807243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wia Unit Of Measure:	1.500 kilohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  135.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  65.0/4275.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Note established  Terminal Length:  1.500 inches  Body Diameter:  0.090 inches  Body Length:  0.220 inches  Power Dissipation Rating in Watts:  5.500 free air  Style Designator:  Avial terminal each end  Test Data Document:  27942-5800/243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Body Line:  Wa  Unit Of Measure:  Demilitarization:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  65.0/4275.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  1.500 inches  Body Diameter:  0.090 inches  Body Length:  2.20 inches  Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  27942-5800/243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.:  excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Via  Unit Of Measure:  — Demilitarization:	-5.000/+5.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  65.01+275.0  Inclosure Method: Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  1.500 inches  Body Diameter:  0.020 inches  Body Diameter:  0.500 free air  Style Designator:  Avail terminal each end  Test Data Document:  Style Designator:  Avail terminal each end  Test Data Document:  Shelf Life:  Wire  Unit Of Measure:  Demilitarization:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius:	135.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  165.0/+275.0  Inclosure Method: Encapsulated Terminal Type:  Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Diameter: 0.090 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.500 ree air Style Designator: Axial terminal each end Test Data Document: 97942-580/243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Avail terminal each end Test Data Document: 37942-5807243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	275.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 97942-5807243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Avial terminal each end Test Data Document: 97942-580r243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	-65.0/+275.0
Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  1.500 inches  Body Diameter:  0.090 inches  Body Length:  0.220 inches  Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  97942-580r243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Inclosure Method:
Wire lead  Reliability Indicator:  Not established  Terminal Length: 1.500 inches  Body Diameter: 0.090 inches  Body Length: 0.220 inches  Power Dissipation Rating In Watts: 0.500 free air  Style Designator:  Axial terminal each end  Test Data Document: 97942-580r243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization:	Encapsulated
Reliability Indicator:  Not established  Terminal Length:  1.500 inches  Body Diameter:  0.090 inches  Body Length:  0.220 inches  Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  27942-580r243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Wa  Unit Of Measure:  Demilitarization:	Terminal Type:
Note stablished  Ferminal Length: 1.500 inches  Body Diameter: 0.090 inches  Body Length: 0.220 inches  Power Dissipation Rating In Watts: 0.500 free air  Style Designator: Axial terminal each end  Test Data Document: 97942-580r243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: Wa  Unit Of Measure: Demilitarization:	Wire lead
Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 97942-580r243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	Reliability Indicator:
1.500 inches Body Diameter: 2.0.990 inches Body Length: 2.0.220 inches Power Dissipation Rating In Watts: 2.500 free air Style Designator: Axial terminal each end Test Data Document: 27942-580r243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	Not established
Body Diameter:  0.090 inches  Body Length: 0.220 inches  Power Dissipation Rating In Watts: 0.500 free air  Style Designator: Axial terminal each end  Test Data Document: 97942-580r243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization:	Terminal Length:
20.090 inches  Body Length:  20.220 inches  Power Dissipation Rating In Watts:  20.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  27942-580r243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	1.500 inches
Body Length: 0.220 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 97942-580r243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Body Diameter:
D.220 inches  Power Dissipation Rating In Watts: D.500 free air  Style Designator:  Axial terminal each end  Test Data Document: D7942-580r243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	0.090 inches
Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  97942-580r243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Body Length:
2.500 free air  Style Designator: Axial terminal each end  Test Data Document: 27942-580r243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization:	0.220 inches
Axial terminal each end  Test Data Document: 97942-580r243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a Unit Of Measure:	Power Dissipation Rating In Watts:
Axial terminal each end  Test Data Document:  97942-580r243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	0.500 free air
Test Data Document: 97942-580r243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a Unit Of Measure: Demilitarization:	Style Designator:
97942-580r243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Test Data Document:
Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	97942-580r243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
N/a Unit Of Measure:  Demilitarization:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization:	Shelf Life:
 Demilitarization:	N/a
	Unit Of Measure:
No	Demilitarization:
	No
Filig:	Fiig:
4001a0	A001a0