NSN 5905-00-600-5193

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-600-5193 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Terminal Length:** 0.250 inches **Body Diameter:** 0.188 inches **Shaft Diameter:** 0.109 inches **Shaft Length:** 0.062 inches **Body Length:** 0.656 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 240.0 **Center To Center Distance Between Terminals:** 1.000 inches **Terminal Location:** Rear end **Mounting Method: Terminal Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 3.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 240.0 **Center To Center Distance Between Center Terminal And Outside Terminal:** 0.500 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Power Dissipation Rating Per Section In Watts:** 1.25 free air single section **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

NSN 5905-00-600-5193

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Stops
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-250.0 to 250.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No