

View Online at https://aerobasegroup.com/nsn/5905-00-602-4819

Section Quantity: 1 Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.859 mils and 0.891 centimeters

Shaft Diameter:

Between 0.1245 inches and 0.1248 inches

Shaft Length:

Between 0.656 inches and 0.719 inches

Mounting Bushing Length:

Between 0.297 inches and 0.328 inches

Body Length:

Between 1.438 inches and 1.458 inches

Shaft Style:

Round

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 3600.0 and 3610.0

Maximum Starting Torque:

0.50 inch-ounces

Maximum Running Torque:

0.40 inch-ounces

Maximum Stop Torque:

100.00 inch-ounces

Shaft End Play:

0.005 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.005 inches

Pilot Diameter Runout:

0.002 inches

Shaft Radial Play:

0.003 inches

Fragility Factor:

Moderately rugged



Screw Thread Diameter: Between 0.234 inches and 0.266 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Standard bushing **Features Provided:** Humidity proof **Cubic Measure:** 0.867 cubic inches **Electrical Resistance Per Section:** 100.0 percent, rated amperes c and better flooring **Rotary Actuator Travel In Angular Deg:** Between 3600.0 and 3610.0 **Function Conformity Tolerance Per Section:** -0.50/+0.50 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Power Dissipation Rating Per Section In Watts:** 3.0 7th secondary quality **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** 7 oclock all primaries Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Precious Material And Location:** Terminal surfaces gold **Precious Material:** Gold **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a Unit Of Measure:



Demilitarization:

No

Fiig:

A002a0