NSN 5905-00-602-5324

Nonprecision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-602-5324 **Section Quantity:** 3 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 1.5610 inches and 1.5620 inches Pilot Length: Between 0.0570 inches and 0.0670 inches **Undercut Diameter:** 1.625 inches **Undercut Width:** 0.0730 inches **Body Diameter:** Between 1.745 inches and 1.755 inches **Shaft Diameter:** 0.124 inches **Shaft Length:** 0.578 inches **Body Length:** 0.875 inches **Mounting Lip Diameter:** Between 1.7450 inches and 1.7550 inches **Mounting Lip Depth:** Between 0.0880 inches and 0.0980 inches **Shaft Style:** Round Switch Type: Rotary **Switch Voltage Rating In Volts:** 115.0 and 115.0 **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 77.0 **Maximum Starting Torque:** 3.00 inch-ounces **Maximum Running Torque:** 3.00 inch-ounces

Maximum Stop Torque: 5.00 inch-ounces

NSN 5905-00-602-5324

Nonprecision Wire Wound Variable Resistor - Page 2 of 3



Shaft Runout:
0.001 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.00100 inches
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Single pole, single throw, normally closed
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
17.0 kilohms all sections
Rotary Actuator Travel In Angular Deg:
94.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 all sections
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 all sections
Power Dissipation Rating Per Section In Watts:
1.0 free air all sections
Resistance Tolerance Per Section In Percent:
-2.0 to 2.0 all sections
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 all sections
Switch Current Type And Rating In Amps:
2.000 ac and 2.000 dc
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
4 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5905-00-602-5324

Nonprecision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0