

View Online at https://aerobasegroup.com/nsn/5905-00-602-9773

Section Quantity:

2

Body Style:

Rectangular bushing mounted

Reliability Indicator:

Not established

Shaft Diameter:

0.312 inches

Shaft Length:

1.062 inches

Mounting Bushing Length:

0.250 inches

Body Length:

4.125 inches

Body Width:

1.812 inches

Body Height:

1.812 inches

Shaft Style:

Round

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

3.00 inch-ounces

Maximum Running Torque:

3.00 inch-ounces

Nonturn Device Location:

At 6 oclock

Nonturn Device Radius:

0.562 inches

Shaft End Play:

0.005 inches

Shaft Runout:

0.0005 inches

Lateral Runout:

0.003 inches

Pilot Diameter Runout:

0.00200 inches



Shaft Radial Play: 0.003 inches Screw Thread Diameter: 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Upper adjacent side single row **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 100.0 kilohms all sections **Rotary Actuator Travel In Angular Deg:** 3600.0 **Function Conformity Tolerance Per Section:** -0.25/+0.25 all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 all sections **Power Dissipation Rating Per Section In Watts:** 5.0 free air all sections **Function Conformity Per Section:** All sections independent linearity **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 all sections **Actuator Travel Control Feature:** Clutch **Function Characteristic Per Section:** All sections linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 all sections Terminal Type And Quantity: 6 tab, solder lug Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0