Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-604-6796

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

### **Overall Length:**

1.672 inches

### Body Diameter:

1.688 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.797 inches

Mounting Bushing Length:

## 0.406 inches

**Body Length:** 

0.875 inches

Shaft Style:

Round

Actuator Type:

Single shaft

### Fragility Factor:

Moderately rugged

### Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

### **Mounting Method:**

Standard bushing

#### **Features Provided:**

Grounded contact arm

## **Electrical Resistance Per Section:**

3.0 kilohms single section

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

80.0 single section

# **Power Dissipation Rating Per Section In Watts:**

1.0 free air single section



**Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A002a0