## NSN 5905-00-604-9608

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-604-9608 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.937 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.625 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.969 inches **Shaft Style:** Round Switch Type: Rotary **Switch Voltage Rating In Volts:** 125.0 **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.438 inches **Switch Operating Position:** Start of rotation **Switch Contact Arrangement:** Single pole, single throw, normally open, both positions maintained **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** 

Rear-bottom

**Mounting Method:** 

Standard bushing

NSN 5905-00-604-9608 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Features Provided:	
Switch	
Electrical Resistance Per Section:	
25.0 kilohms single section	
Power Dissipation Rating Per Section In Watts:	
0.5 free air single section	
Resistance Tolerance Per Section In Percent:	
20.0 to 20.0 single section	
Switch Current Type And Rating In Amps:	
3.000 ac/dc	
Standard Taper Curve Per Section:	
A single section	
Terminal Type And Quantity:	
5 tab, solder lug	
Shelf Life:	
N/a	
Unit Of Measure:	
<del>.</del>	
Demilitarization:	
No	
Fiig:	
A002a0	