NSN 5905-00-606-0893

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-606-0893

| Section Quantity |
|--|
| Section Quantity: |
| Body Style: |
| Cylindrical servo mounted |
| Reliability Indicator: |
| Not established |
| Pilot Diameter: |
| Between 1.3110 inches and 1.3120 inches |
| Pilot Length: |
| Between 0.0570 inches and 0.0670 inches |
| Overall Length: |
| 2.750 inches |
| Undercut Diameter: |
| 1.310 inches |
| Undercut Width: |
| Between 0.0680 inches and 0.0780 inches |
| Body Diameter: |
| Between 1,422 inches and 1,453 inches |
| Shaft Diameter: |
| 0.250 inches |
| Shaft Length: |
| Between 0.344 inches and 0.406 inches |
| Body Length: |
| 2.125 inches |
| Overall Diameter: |
| 2.000 inches |
| Mounting Lip Diameter: |
| Between 1.4320 inches and 1.4420 inches |
| Mounting Lip Depth: |
| Between 0.0880 inches and 0.0980 inches |
| Shaft Style: |
| Round |
| Actuator Type: |
| Single shaft |
| Effective Electrical Rotation In Deg Angular Rotation: |
| 354.0 |
| Maximum Starting Torque: |
| 6.00 inch-ounces |
| Maximum Running Torque: |
| 3.00 inch-ounces |
| Shaft Runout: |

0.001 inches

NSN 5905-00-606-0893

Precision Wire Wound Variable Resistor - Page 2 of 2



| Pilot Diameter Runout: |
|---|
| 0.00100 inches |
| Terminal Location: |
| Radially positioned over more than half the circumference |
| Mounting Method: |
| Clamp ring |
| Features Provided: |
| Nonmetallic shaft |
| Electrical Resistance Per Section: |
| 5.0 percent, rated amperes c and better industrial clears |
| Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation: |
| 177.0 all sections |
| Rotary Actuator Travel In Angular Deg: |
| 360.0 |
| Function Conformity Tolerance Per Section: |
| -0.15/+0.15 all sections |
| Power Dissipation Rating Per Section In Watts: |
| 3.0 free air all sections |
| Function Conformity Per Section: |
| All sections independent linearity |
| Fixed Tap Quantity Per Section: |
| 1 3rd section |
| Resistance Tolerance Per Section In Percent: |
| -5.0/+5.0 all sections |
| Actuator Travel Control Feature: |
| Stops |
| Tap Location From Ccw Terminal Per Section In Ohms: |
| 2500.0 all sections |
| Function Characteristic Per Section: |
| All sections linear |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 40.0 all sections |
| Terminal Type And Quantity: |
| 12 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A002a0 |