## NSN 5905-00-606-0893

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-606-0893

Section Quantity
Section Quantity:
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
Between 1.3110 inches and 1.3120 inches
Pilot Length:
Between 0.0570 inches and 0.0670 inches
Overall Length:
2.750 inches
Undercut Diameter:
1.310 inches
Undercut Width:
Between 0.0680 inches and 0.0780 inches
Body Diameter:
Between 1,422 inches and 1,453 inches
Shaft Diameter:
0.250 inches
Shaft Length:
Between 0.344 inches and 0.406 inches
Body Length:
2.125 inches
Overall Diameter:
2.000 inches
Mounting Lip Diameter:
Between 1.4320 inches and 1.4420 inches
Mounting Lip Depth:
Between 0.0880 inches and 0.0980 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
354.0
Maximum Starting Torque:
6.00 inch-ounces
Maximum Running Torque:
3.00 inch-ounces
Shaft Runout:

0.001 inches

## NSN 5905-00-606-0893

Precision Wire Wound Variable Resistor - Page 2 of 2



Pilot Diameter Runout:
0.00100 inches
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
5.0 percent, rated amperes c and better industrial clears
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
177.0 all sections
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.15/+0.15 all sections
Power Dissipation Rating Per Section In Watts:
3.0 free air all sections
Function Conformity Per Section:
All sections independent linearity
Fixed Tap Quantity Per Section:
1 3rd section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 all sections
Actuator Travel Control Feature:
Stops
Tap Location From Ccw Terminal Per Section In Ohms:
2500.0 all sections
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 all sections
Terminal Type And Quantity:
12 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0