## NSN 5905-00-606-0894

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-606-0894 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.6250 inches Pilot Length: 0.0620 inches **Overall Length:** 1.949 inches **Undercut Diameter:** 0.781 inches **Undercut Width:** 0.0630 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.1248 inches **Shaft Length:** 0.375 inches **Body Length:** 1.574 inches **Overall Diameter:** 1.070 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 

0.60 inch-ounces

**Maximum Running Torque:** 

0.50 inch-ounces

## NSN 5905-00-606-0894

Precision Wire Wound Variable Resistor - Page 2 of 3



| Shaft End Play:   |
|---|
| 0.005 inches  |
| Shaft Runout:   |
| 0.001 inches  |
| Lateral Runout:   |
| 0.003 inches  |
| Pilot Diameter Runout:  |
| 0.00150 inches  |
| Shaft Radial Play:  |
| 0.002 inches  |
| Terminal Location:  |
| Longitudinally positioned on the circumference                                      |
| Mounting Method:  |
| Clamp ring  |
| Features Provided:  |
| Humidity proof  |
| Electrical Resistance Per Section:  |
| 10.0 kilohms single section   |
| Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation: |
| 1800.0 single section   |
| Rotary Actuator Travel In Angular Deg:  |
| 3600.0  |
| Function Conformity Tolerance Per Section:  |
| -0.50/+0.50 single section  |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:         |
| 85.0 single section   |
| Power Dissipation Rating Per Section In Watts:                                      |
| 1.5 free air single section   |
| Function Conformity Per Section:  |
| Single section independent linearity  |
| Fixed Tap Quantity Per Section:   |
| 1 single section  |
| Tap Location Tolerance Per Section:   |
| -2.0/+2.0 degrees angular rotation single section                                   |
| Resistance Tolerance Per Section In Percent:  |
| -5.0/+5.0 single section  |
| Actuator Travel Control Feature:  |
| Stops   |
| Function Characteristic Per Section:  |
| Single section linear   |
| Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:      |
| +0.0/+130.0 single section  |

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

## NSN 5905-00-606-0894

Precision Wire Wound Variable Resistor - Page 3 of 3



| Terminal Type And Quantity: |
|-----------------------------|
| 4 turret                    |
| Shelf Life:                 |
| N/a                         |
| Unit Of Measure:            |
|                             |
| Demilitarization:           |
| No                          |
|                             |

Fiig:

A002a0