## NSN 5905-00-606-0894

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-606-0894 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.6250 inches Pilot Length: 0.0620 inches **Overall Length:** 1.949 inches **Undercut Diameter:** 0.781 inches **Undercut Width:** 0.0630 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.1248 inches **Shaft Length:** 0.375 inches **Body Length:** 1.574 inches **Overall Diameter:** 1.070 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 

0.60 inch-ounces

**Maximum Running Torque:** 

0.50 inch-ounces

## NSN 5905-00-606-0894

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.005 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.003 inches
Pilot Diameter Runout:
0.00150 inches
Shaft Radial Play:
0.002 inches
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Clamp ring
Features Provided:
Humidity proof
Electrical Resistance Per Section:
10.0 kilohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
1800.0 single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-2.0/+2.0 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
+0.0/+130.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

## NSN 5905-00-606-0894

Precision Wire Wound Variable Resistor - Page 3 of 3



Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

A002a0